


| | | |
|-----------------------------|--|------|
| PRODUCT NAME | Commercial Freezer (Table Type) | |
| MODEL | YRW-152FMC-TH | |
| POWER SUPPLY | Single Phase 220V 50Hz | |
| OUTSIDE DIMENSIONS | (W) 1500mm x (D) 750mm x (H) 800mm | |
| INSIDE DIMENSIONS | (W) 1136mm x (D) 603mm x (H) 595mm | |
| EFFECTIVE CAPACITY | 426L | |
| WEIGHT | 105kg | |
| EXTERIOR MATERIAL | Stainless Steel (Front and Sides) Stainless Steel (Top) Galvanized Steel (Rear and Bottom) | |
| INTERIOR MATERIAL | Stainless Steel | |
| DOOR MATERIAL | Stainless Steel (Front) ABS Resin, Magnet-Style Packing (Rear) | |
| INSULATION MATERIAL | Polyurethane Foam | |
| ADJUSTABLE SHELF MATERIAL | Steel Wire Resin coating | |
| COOLING PERFORMANCE | -25°C to -15°C (No Load and Ambient Temperature of 30°C) | |
| COMPRESSOR | 425W | |
| REFRIGERANT CONTROL METHOD | Capillary Tube | |
| CONDENSER | Fin and Tube Type, Forced Air-Cooling | |
| EVAPORATOR | Fin and Tube Type, Forced Cold Air Circulation | |
| REFRIGERANT | R-404A | |
| TEMPERATURE CONTROL | Microcomputer Control, Digital Display | |
| DEFROST CONTROL | Microcomputer Control Defrost Heater | |
| APPLICABLE BREAKER CAPACITY | Single Phase 220V 15A 50Hz | |
| POWER CORD | 2.0m (Plug with Earth Wire) | |
| VOLTAGE RANGE | 220V $\pm 6\%$ | |
| COOLING | Operation Current | 1.9A |
| | Starting Current | 11A |
| | Power Consumption | 360W |
| | Power Factor | 85% |
| DEFROSTING | Operation Current | 1.0A |
| | Power Consumption | 210W |
| OPERATING TEMPERATURE RANGE | 5°C to 35°C | |
| RADIATION OF HEAT CAPACITY | 705W | |
| ADJUSTABLE LEG | Resin made Leg form 95 to 130mm | |
| ACCESSORIES | Shelves (4 Pieces) Drain Accessory (1 Set) | |
| OTHER ACCESSORIES | Condenser Filter | |

We may change it without a notice for improvement about the specifications and design.

→ SUCTION AIR
→ EXHAUST AIR

PLUG TYPE



| REFERENCE NO |
|---|
| DATA 08 · 06 · 2020 SCALE 1 / 20 DRAWING NO |

GALILEI (THAILAND) CO., LTD.