


PRODUCT NAME	Commercial Refrigerator (Table Type)	
MODEL	YRN-160RMPC-TH	
POWER SUPPLY	Single Phase 220V 50Hz	
OUTSIDE DIMENSIONS	(W) 1650mm x (D) 660mm x (H) 800mm	
INSIDE DIMENSIONS	(W) 1286mm x (D) 513mm x (H) 595mm	
EFFECTIVE CAPACITY	417L	
WEIGHT	100kg	
EXTERIOR MATERIAL	Stainless Steel (Front and Sides) Stainless Steel (Top) Galvanized Steel (Rear and Bottom)	
INTERIOR MATERIAL	Stainless Steel	
DOOR MATERIAL	Stainless Steel (Front) Stainless Steel (Rear)	
INSULATION MATERIAL	Polyurethane Foam	
ADJUSTABLE SHELF MATERIAL	Steel Wire Resin coating	
COOLING PERFORMANCE	-5°C to 10°C (No Load and Ambient Temperature of 30°C)	
COMPRESSOR	140W	
REFRIGERANT CONTROL METHOD	Capillary Tube	
CONDENSER	Fin and Tube Type, Forced Air-Cooling	
EVAPORATOR	Fin and Tube Type, Forced Cold Air Circulation	
REFRIGERANT	R-134a	
TEMPERATURE CONTROL	Microcomputer Control, Digital Display	
DEFROST CONTROL	Microcomputer Control Defrost Heater	
APPLICABLE BREAKER CAPACITY	Single Phase 220V 15A 50Hz	
POWER CORD	2.0m (Plug with Earth Wire)	
VOLTAGE RANGE	220V±6%	
COOLING	Operation Current	1.1A
	Starting Current	12A
	Power Consumption	235W
DEFROSTING	Operation Current	0.9A
	Power Consumption	207W
OPERATING TEMPERATURE RANGE	5°C to 35°C	
RADIATION OF HEAT CAPACITY	510W	
ADJUSTABLE LEG	Resin made Leg form 95 to 130mm	
ACCESSORIES	Shelves (6 Pieces)	
	Receiving Brackets (6 Sets)	
	Locking Devices (2 Sets) Drain Accessory (1 Set)	
OTHER ACCESSORIES	Condenser Filter	

We may change it without a notice for improvement about the specifications and design.
Not include GN Pans.



		REFERENCE NO
DATA 08 . 06 . 2020	SCALE 1/20	DRAWING NO
GALILEI (THAILAND) CO., LTD.		