


PRODUCT NAME	Commercial Refrigerator Showcase	
MODEL	LGC-120REA-TH	
POWER SUPPLY	Single Phase 220V 50Hz	
OUTSIDE DIMENSIONS	(W) 1200mm× (D) 600mm× (H) 800mm	
INSIDE DIMENSIONS	(W) 947mm× (D) 514mm× (H) 620mm	
EFFECTIVE CAPACITY	293L	
WEIGHT	85kg	
EXTERIOR MATERIAL	Color Steel (Front and Sides) Stainless Steel (Top) Galvanized Steel (Rear and Bottom)	
INTERIOR MATERIAL	Color Steel	
DOOR MATERIAL	Slide Type Pair Glass	
INSULATION MATERIAL	Polyurethane Foam	
ADJUSTABLE SHELF MATERIAL	Steel Wire Resin coating	
COOLING PERFORMANCE	2°C to 10°C (No Load and Ambient Temperature of 30°C)	
COMPRESSOR	140W	
REFRIGERANT CONTROL METHOD	Capillary Tube	
CONDENSER	Fin and Tube Type, Forced Air-Cooling	
EVAPORATOR	Fin and Tube Type, Forced Cold Air Circulation	
REFRIGERANT	R-134a	
TEMPERATURE CONTROL	Microcomputer Control, Digital Display	
DEFROST CONTROL	Microcomputer Control Offcycle Defrost	
APPLICABLE BREAKER CAPACITY	Single Phase 220V 15A 50Hz	
POWER CORD	2.0m (Plug with Earth Wire)	
VOLTAGE RANGE	220V±6%	
COOLING	Operation Current	1.4A
	Starting Current	11A
	Power Consumption	220W
	Power Factor	71%
DEFROSTING	Operation Current	_____
	Power Consumption	_____
OPERATING TEMPERATURE RANGE	5°C to 35°C	
RADIATION OF HEAT CAPACITY	515W	
ADJUSTABLE LEG	Resin made Leg form 95 to 130mm	
ACCESSORIES	Shelves (4 Pieces)	
	Drain Pan Drain Accessory (1 Set)	
OTHER ACCESSORIES	Condenser Filter Internal Lighting (LED)	

We may change it without a notice for improvement about the specifications and design.

- ◻ SUCTION AIR
- ◼ EXHAUST AIR

PLUG TYPE



		REFERENCE NO
DATA 02 . 02 . 2020	SCALE 1/20	DRAWING NO
<b>GALILEI (THAILAND) CO., LTD.</b>		