

- 1. Ambient temperature: 27°C, humidity: 70%, wind speed: 0.2 m/s or less

 If the above installation conditions are exceeded, wastewater treatment is required Approximate temperature: 25°C, 80% (during rainy season),

 Discard the water in the drain pan once a day.
- 2. The evaporator cloth of the evaporator is a consumable item. As a rule of thumb, it needs to be replaced in about 2 years. Depending on the environment, the performance of the evaporating cloth may deteriorate and need to be replaced after about one year.
 3. The back sideunit will have a higher ambient temperature due to exhaust heat.
- 3. The back sideunit will have a higher ambient temperature due to exhaust heat.

 Please be careful about the display of surrounding products
- 4. We may change it without a notice for improvement about the specifications and design.

PRODUCT NAME	Commercial Refrigerator Showcase			
MODEL	MEK-3AGKJA5L-TH			
POWER SUPPLY	Single Phase 220V 50Hz			
OUTSIDE DIMENSIONS	(W) 900mm× (D) 750mm× (H) 1900mm			
INSIDE DIMENSIONS	(W) 855mm× (D) 469mm× (H) 1310mm			
EFFECTIVE CAPACITY	5 3 9 L			
SHELF	Steel Plate Shelf (Variable 0 ° or 8°)			
DISPLAY AREA	2. 31 m ²			
WEIGHT	200kg			
	Color Steel, Painted Steel			
EXTERIOR MATERIAL	Galvanized Steel, Pair Glass			
	Resin Molded Product			
INTERIOR MATERIAL	Color Steel, Painted Steel			
INSULATION MATERIAL	Polyurethane Foam			
	Temperature 27°C OR LESS			
AMBIENT AIR CONDITION	, ,			
	Wind Speed 0.2m/s OR LESS			
COOLING PERFORMANCE	3°C t o 20°C			
COMPRESSOR	(No Load and Within Ambient Air Condition) 770W (DC Inverter)			
REFRIGERANT CONTROL METHOD	Electronic Expansion Valve			
CONDENSER	Fin and Tube Type, Forced Air-Cooling			
EVAPORATOR	Fin and Tube Type, Forced Cold Air Circulation			
REFRIGERANT	R-404A			
	Microcomputer Control, Digital Display			
DEFROST CONTROL	Microcomputer Control Offcycle Defrost			
	Single Phase 220V 15A 50Hz			
POWER CORD	2. Om (Plug with Earth Wire)			
VOLTAGE RANGE	220V±6%			
	Operation Current 3.9A			
	Maximum Current 6.5A			
COOLING	Power Consumption 825W			
	Power Factor 95%			
	Operation Current 1.6A			
DEFROSTING	Power Consumption 312W			
RADIATION OF HEAT CAPACITY	3 0 5 0 W			
	Alarm Buzzer (Standard Equipment)			
	Night Cover			
ACCESSORIES	Caster			
	Drain Pan			
	Drain Evaporator			
OTHER ACCESSORIES	Condenser Filter			
AUGESSORIES	Internal Lighting (LED: 8.5W×1)			

SUCTION AIR

EXHAUST AIR



							REFERENCE NO
DATA	0 5		0 4	2021	SCALE	1/20	DRAWING NO
		_		_ ,_			- \

GALILEI (THAILAND) CO., LTD.