

- 1. Ambient temperature: 27°C, humidity: 70%, wind speed: 0.2 m/s or less If the above installation conditions are exceeded, wastewater treatment is required Approximate temperature: 25%, 80% (during rainy season), Discard the water in the drain pan once a day.
- 2. The evaporator cloth of the evaporator is a consumable item. As a rule of thumb, it needs to be replaced in about 2 years. Depending on the environment, the performance of the evaporating cloth may deteriorate and need to be replaced after about one year. 3. The back sideunit will have a higher ambient temperature due to exhaust heat.
- Please be careful about the display of surrounding products
- 4. We may change it without a notice for improvement about the specifications and design.

PRODUCT NAME	Commercial Refrigerator Showcase				
MODEL	MEK-4AGKJA5L-TH				
POWER SUPPLY	Single Phase 220V 50Hz				
OUTSIDE DIMENSIONS	(W) 1200mm× (D) 750mm× (H) 1900mm				
INSIDE DIMENSIONS	(W) 1155mm× (D) 469mm× (H) 1310mm				
EFFECTIVE CAPACITY	7 2 7 L				
SHELF	Steel Plate Shelf (Variable 0 ° or 8°)				
DISPLAY AREA	3. 13 m ²				
WEIGHT	2 4 5 k g				
	Color Steel, Painted Steel				
EXTERIOR MATERIAL	Galvanized Steel, Pair Glass				
	Resin Molded Product				
INTERIOR MATERIAL	Color Steel, Painted Steel				
INSULATION MATERIAL	Polyurethane Foam				
	Temperature 27°C OR LESS				
AMBIENT AIR CONDITION	Humidity 70% OR LESS				
	Wind Speed 0. 2m/s OR LESS				
COOLING PERFORMANCE	3°C to 20°C (No Load and Within Ambient Air Condition)				
COMPRESSOR	1250W (DC Inverter)				
REFRIGERANT CONTROL METHOD	Electronic Expansion Valve				
CONDENSER	Fin and Tube Type, Forced Air-Cooling				
EVAPORATOR	Fin and Tube Type, Forced Cold Air Circulation				
REFRIGERANT	R-404A				
TEMPERATURE CONTROL	Microcomputer Control, Digital Display				
DEFROST CONTROL	Microcomputer Control Offcycle Defrost				
APPLICABLE BREAKER CAPACITY	Single Phase 220V 15A 50Hz				
POWER CORD	2. Om (Plug with Earth Wire)				
VOLTAGE RANGE	2 2 0 V ± 6 %				
	Operation Current 6.8A				
COOLING	Maximum Current 9.5A				
COOLING	Power Consumption 1460W				
	Power Factor 97%				
DEEDOSTING	Operation Current 2.2A				
DEFROSTING	Power Consumption 447W				
RADIATION OF HEAT CAPACITY	4 8 4 0 W				
	Alarm Buzzer (Standard Equipment)				
	Night Cover				
ACCESSORIES	Caster				
	Drain Pan				
	Drain Evaporator				
OTHER ACCESSORIES	Condenser Filter				
	Internal Lighting (LED: 11. 2W×1)				

SUCTION AIR

EXHAUST AIR



							REFERENCE NO
DATA	0 5		0 4	2021	SCALE	1/20	DRAWING NO
		_		. , _			->

GALILEI (THAILAND) CO., LTD.